

Schuller Eh'klar GmbH
 AUSTRIA
 Im Astenfeld 6
 A – 4490 St. Florian
 Tel.(0043) 07224/68 200
 Fax(0043) 07224/68 282
 E-Mail: office@schuller.eu
 www.schuller.eu

**Schuller
 Eh'klar**



St. Florian, 04.11.2013

UV-PAINT-MASKER

(Artikelnummer: 45880, 45881, 45882, 45884, 45885, 45887, 45888, 45889)

Short description:

A high quality fabric carrier made of polyester and cotton coated with a special adhesive with high adhesive power even at low temperatures. Good adhesion on smooth and rough surfaces. Further outstanding features are the good rolling properties and the strong, low-stretch carrier.

The perforated HDPE film with electrostatic treatment adheres to most of the surfaces and prevents paint flaking and other contaminations.

Product data adhesive tape:

Material	Coated fabric	
Adhesive	UV-stabilized natural rubber	
Total thickness	70 mesh width (ca. 300my)	
Adhesion to steel	8,8 N/25mm	
Tensile strenght	118 N/25mm	
Elongation at break	11%	
Temperature resistance	until +85°C (180min.)	
UV-resistance	Indoor until 4 weeks max.	
UV-resistance	Outdoor until 2 weeks max.	

Product data HDPE Foil:

Total thickness	8-10 my HDPE foil, transparent	
Treatment	statically charged	

Aplication:

The UV-PAINT-MASKER protects against dashes, paint drops and other contaminations. By the UV resistance, it's ideal for indoor and outdoor usage. They could be problems at carbon and porous materials (stone, wood...), therefore it is essential to do a relevant test adhesion before doing the actual work.

Conditions:

Store in a cool and dry place, away from sunlight and direct heat sources (15-23°C / 50% relative humidity). As far as the storage conditions are respected, the product is garanted 12 months.