



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 27

Ceresit CT 16 BASE

SDS No. : 686345
V003.0

Revision: 09.11.2021

printing date: 15.10.2022

Replaces version from: 25.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ceresit CT 16 BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Paint

1.3. Details of the supplier of the safety data sheet

Henkel Polska Sp. z o.o.

ul. Domaniewska 41

02-672 Warszawa

Poland

Phone: +48 (22) 5656 200

Fax-no.: +48 (22) 5656 666

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Specific target organ toxicity - repeated exposure

Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Quartz (SiO₂) respirable particulates (RCS) >=10%

Signal word:	Warning
Hazard statement:	H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust. Contains: Isothiazolinone mixture 3:1 (CIT/MIT) May produce an allergic reaction.
Precautionary statement: Prevention	P260 Do not breathe mist/vapours. P262 Do not get in eyes, on skin, or on clothing. P273 Avoid release to the environment.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Primer

Base substances of preparation:

Inorganic fillers

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Quartz (SiO ₂) respirable particulates (RCS) >=10% 14808-60-7	238-878-4	1- < 10 %	STOT RE 1 H372
Quartz (SiO ₂), <1% respirable 14808-60-7	238-878-4	1- < 10 %	
Titanium dioxide 13463-67-7	236-675-5 01-2119489379-17	1- < 5 %	Carc. 2; Inhalation H351
Chromium (III) oxide 1308-38-9	215-160-9 01-2119433951-39	1- < 5 %	
Chrome antimony titanium buff rutile 68186-90-3	269-052-1 01-2119491294-33	1- < 5 %	
Triiron tetraoxide 1317-61-9	215-277-5 01-2119457646-28	1- < 5 %	
Bismuth vanadium tetraoxide 14059-33-7	237-898-0 01-2119486965-17	1- < 5 %	STOT RE 2; Inhalation H373
trizinc bis(orthophosphate) 7779-90-0	231-944-3 01-2119485044-40	0,1- < 1 %	Aquatic Chronic 1 H410 Aquatic Acute 1 H400
3-iodo-2-propynyl butylcarbamate 55406-53-6	259-627-5 01-2120762115-60	0,01- < 0,25 %	Aquatic Chronic 1 H410 STOT RE 1 H372 Acute Tox. 3; Inhalation H331 Skin Sens. 1 H317 Eye Dam. 1 H318 Aquatic Acute 1 H400 Acute Tox. 4; Oral H302 STOT SE 3 H335 M factor (Acute Aquat Tox): 10
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	01-2119473797-19	0,01- < 0,1 %	Skin Corr. 1B H314 Acute Tox. 4; Oral H302 STOT RE 2; Oral H373 Aquatic Acute 1 H400 STOT SE 3 H335 Asp. Tox. 1 H304 Eye Dam. 1 H318 Aquatic Chronic 2 H411 M factor (Acute Aquat Tox): 10
pyrithione zinc 13463-41-7	236-671-3 01-2119511196-46	0,0001- < 0,01 % (1 ppm- < 100 ppm)	Repr. 1B H360D Aquatic Chronic 1 H410 Eye Dam. 1 H318 STOT RE 1 H372 Acute Tox. 2; Inhalation H330 Aquatic Acute 1 H400 Acute Tox. 3; Oral H301

Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	01-2120764691-48	0,0001- < 0,0015 % (1 ppm- < 15 ppm)	M factor (Acute Aquat Tox): 1.000 M factor (Chron Aquat Tox): 10 Acute Tox. 2; Inhalation H330 Aquatic Chronic 1 H410 Acute Tox. 3; Oral H301 Acute Tox. 2; Dermal H310 Eye Dam. 1 H318 Skin Sens. 1A H317 Aquatic Acute 1 H400 Skin Corr. 1C H314 M factor (Acute Aquat Tox): 100 M factor (Chron Aquat Tox): 100
---	------------------	---	---

**For full text of the H - statements and other abbreviations see section 16 "Other information".
 Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Store in a cool, dry place.

Protect from freezing.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection

8.1. Control parameters**Occupational Exposure Limits**

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Dolomite 16389-88-1 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Dolomite 16389-88-1 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO ₂) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII
Quartz (SiO ₂) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII
Chromium (III) oxide 1308-38-9 [CHROMIUM (III) COMPOUNDS (AS CR)]		0,5	Time Weighted Average (TWA):		EH40 WEL
Chromium (III) oxide 1308-38-9 [CHROMIUM METAL, INORGANIC CHROMIUM(II) COMPOUNDS AND INORGANIC CHROMIUM(III) COMPOUNDS (INSOLUBLE)]		2	Time Weighted Average (TWA):	Indicative	ECTLV
Chromium (III) oxide 1308-38-9 [Chromium (II) compounds (as Cr)]		0,5	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Chrome antimony titanium buff rutile 68186-90-3 [Antimony and compounds except stibine (as Sb)]		0,5	Time Weighted Average (TWA):		EH40 WEL
Chrome antimony titanium buff rutile 68186-90-3		0,5	Time Weighted Average (TWA):		EH40 WEL

[Chromium (III) compounds (as Cr)]					
Chrome antimony titanium buff rutile 68186-90-3 [CHROMIUM METAL, INORGANIC CHROMIUM(II) COMPOUNDS AND INORGANIC CHROMIUM(III) COMPOUNDS (INSOLUBLE)]		2	Time Weighted Average (TWA):	Indicative	ECLTV
Cobalt aluminate blue spinel 1345-16-0 [COBALT AND COBALT COMPOUNDS (AS CO)]		0,1	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [ROUGE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [ROUGE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		5	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		10	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Dolomite 16389-88-1 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Dolomite 16389-88-1 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII
Quartz (SiO ₂) 14808-60-7 [SILICA, CRYSTALLINE (CRISTOBALITE, QUARTZ, TRIDYMITE, TRIPOLI)]		0,1	Time Weighted Average (TWA):	Binding OELV	IR_OEL
Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST]		0,1	Time Weighted Average (TWA):		EU OELIII
Quartz (SiO ₂) 14808-60-7 [SILICA, CRYSTALLINE (CRISTOBALITE, QUARTZ, TRIDYMITE, TRIPOLI)]		0,1	Time Weighted Average (TWA):	Binding OELV	IR_OEL
Chromium (III) oxide 1308-38-9 [CHROMIUM METAL, INORGANIC CHROMIUM(II) COMPOUNDS AND INORGANIC CHROMIUM(III) COMPOUNDS (INSOLUBLE)]		2	Time Weighted Average (TWA):	Indicative	ECLTV
Chromium (III) oxide 1308-38-9 [CHROMIUM (III) COMPOUNDS]		2	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Chromium (III) oxide 1308-38-9 [CHROMIUM (II) COMPOUNDS]		2	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Titanium dioxide 13463-67-7		10	Time Weighted Average (TWA):		IR_OEL

[TITANIUM DIOXIDE]					
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL
Chrome antimony titanium buff rutile 68186-90-3 [CHROMIUM (III) COMPOUNDS]		2	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Chrome antimony titanium buff rutile 68186-90-3 [CHROMIUM METAL, INORGANIC CHROMIUM(II) COMPOUNDS AND INORGANIC CHROMIUM(III) COMPOUNDS (INSOLUBLE)]		2	Time Weighted Average (TWA):	Indicative	ECLTV
Diiron trioxide 1309-37-1 [IRON OXIDE]		5	Time Weighted Average (TWA):		IR_OEL
Diiron trioxide 1309-37-1 [ROUGE RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Diiron trioxide 1309-37-1 [IRON OXIDE]		10	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Diiron trioxide 1309-37-1 [ROUGE]		10	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Titanium dioxide 13463-67-7	aqua (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	aqua (marine water)						no hazard identified
Titanium dioxide 13463-67-7	sewage treatment plant (STP)						no hazard identified
Titanium dioxide 13463-67-7	sediment (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	sediment (marine water)						no hazard identified
Titanium dioxide 13463-67-7	Soil						no hazard identified
Titanium dioxide 13463-67-7	Aquatic (intermit. releases)						no hazard identified
Titanium dioxide 13463-67-7	Predator						no hazard identified
Chromium (III) oxide 1308-38-9	Soil				3,2 mg/kg		
Chromium (III) oxide 1308-38-9	sewage treatment plant (STP)		10 mg/l				
Chromium (III) oxide 1308-38-9	sediment (marine water)				1,31 mg/kg		
Chromium (III) oxide 1308-38-9	aqua (marine water)		0,0047 mg/l				
Chromium (III) oxide 1308-38-9	aqua (intermittent releases)		0,0047 mg/l				
Chromium (III) oxide 1308-38-9	sediment (freshwater)				18,2 mg/kg		
Chromium (III) oxide 1308-38-9	aqua (freshwater)		0,0047 mg/l				
Chrome antimony titanium buff rutile 68186-90-3	aqua (freshwater)		0,1 mg/l				
Chrome antimony titanium buff rutile 68186-90-3	aqua (marine water)		0,01 mg/l				
Chrome antimony titanium buff rutile 68186-90-3	sewage treatment plant (STP)		1000 mg/l				
Chrome antimony titanium buff rutile 68186-90-3	aqua (intermittent releases)		1 mg/l				
Bismuth vanadium tetraoxide 14059-33-7	sewage treatment plant (STP)		10000 mg/l				
Trizinc bis(orthophosphate) 7779-90-0	aqua (freshwater)		0,0206 mg/l				
Trizinc bis(orthophosphate) 7779-90-0	aqua (marine water)		0,0061 mg/l				
Trizinc bis(orthophosphate) 7779-90-0	sewage treatment plant (STP)		0,1 mg/l				
Trizinc bis(orthophosphate) 7779-90-0	sediment (freshwater)				117,8 mg/kg		
Trizinc bis(orthophosphate) 7779-90-0	sediment (marine water)				56,5 mg/kg		
Trizinc bis(orthophosphate) 7779-90-0	Soil				35,6 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	aqua (freshwater)		0,00026 mg/l				
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Soil				10 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sewage treatment plant (STP)		0,550 mg/l				
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sediment (freshwater)				3,76 mg/kg		

Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sediment (marine water)				0,376 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	aqua (marine water)		0,000026 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (freshwater)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (marine water)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (freshwater)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (marine water)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Soil				0,01 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (intermittent releases)		0,00339 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Chromium (III) oxide 1308-38-9	Workers	Inhalation	Acute/short term exposure - local effects		2 mg/m ³	
Chromium (III) oxide 1308-38-9	Workers	Inhalation	Long term exposure - local effects		0,5 mg/m ³	
Chromium (III) oxide 1308-38-9	General population	Inhalation	Long term exposure - local effects		0,5 mg/m ³	
Chrome antimony titanium buff rutile 68186-90-3	Workers	inhalation	Long term exposure - local effects		4 mg/m ³	
Chrome antimony titanium buff rutile 68186-90-3	General population	inhalation	Long term exposure - local effects		3 mg/m ³	
Triiron tetraoxide 1317-61-9	Workers	inhalation	Long term exposure - local effects		10 mg/m ³	
Bismuth vanadium tetraoxide 14059-33-7	Workers	inhalation	Long term exposure - local effects		0,02 mg/m ³	
Bismuth vanadium tetraoxide 14059-33-7	General population	inhalation	Long term exposure - local effects		0,005 mg/m ³	
Trizinc bis(orthophosphate) 7779-90-0	Workers	inhalation	Long term exposure - systemic effects		5 mg/m ³	
Trizinc bis(orthophosphate) 7779-90-0	Workers	dermal	Long term exposure - systemic effects		83 mg/kg	
Trizinc bis(orthophosphate) 7779-90-0	General population	inhalation	Long term exposure - systemic effects		2,5 mg/m ³	
Trizinc bis(orthophosphate) 7779-90-0	General population	dermal	Long term exposure - systemic effects		83 mg/kg	
Trizinc bis(orthophosphate) 7779-90-0	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	Inhalation	Long term exposure - systemic effects		0,38 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	inhalation	Long term exposure - local effects		1 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	inhalation	Acute/short term exposure - local effects		1 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	General population	inhalation	Long term exposure - systemic effects		0,035 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	General population	oral	Long term exposure - systemic effects		40 µg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	General	oral	Long term		0,09 mg/kg	

methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	population		exposure - systemic effects			
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

Perforation time > 480 minutes

material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	paste paste varied, according to coloration
Odor	characteristic
Odour threshold	No data available / Not applicable
pH (20 °C (68 °F); Conc.: 100 % product)	7,5 - 8,5
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	Not applicable
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,35 - 1,65 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable

Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Solubility (qualitative)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; 20 °C (68 °F))	4.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable
max. VOC content:

17 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Quartz (SiO ₂) respirable particulates (RCS) >=10% 14808-60-7	LD50	> 22.500 mg/kg	rat	not specified
Quartz (SiO ₂), <1% respirable 14808-60-7	LD50	> 5.050 mg/kg	rat	not specified
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Chromium (III) oxide 1308-38-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Chrome antimony titanium buff rutile 68186-90-3	LD50	> 10,000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Triiron tetraoxide 1317-61-9	LD50	> 5.000 mg/kg	rat	not specified
Bismuth vanadium tetraoxide 14059-33-7	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
trizinc bis(orthophosphate) 7779-90-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3-iodo-2-propynyl butylcarbamate 55406-53-6	LD50	1.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	LD50	1.689 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
pyrithione zinc 13463-41-7	Acute toxicity estimate (ATE)	221 mg/kg		Expert judgement
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Quartz (SiO ₂) respirable particulates (RCS) >=10% 14808-60-7	LD50	> 5.000 mg/kg	rat	not specified
Quartz (SiO ₂), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
Titanium dioxide 13463-67-7	LD50	>= 10.000 mg/kg	hamster	not specified
3-iodo-2-propynyl butylcarbamate 55406-53-6	LD50	> 2.000 mg/kg	rabbit	EPA OPP 81-2 (Acute Dermal Toxicity)
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
pyrithione zinc 13463-41-7	LD50	> 2.000 mg/kg	rat	EPA OPP 81-2 (Acute Dermal Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
Chromium (III) oxide 1308-38-9	LC50	> 5,41 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Triiron tetraoxide 1317-61-9	LC50	> 5,05 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Bismuth vanadium tetraoxide 14059-33-7	LC50	> 5,15 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
3-iodo-2-propynyl butylcarbamate 55406-53-6	LC50	0,68 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
pyrithione zinc 13463-41-7	Acute toxicity estimate (ATE)	0,14 mg/l	dust/mist	4 h		Expert judgement
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Chromium (III) oxide 1308-38-9	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Triiron tetraoxide 1317-61-9	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
trizinc bis(orthophosphate) 7779-90-0	not irritating			Expert judgement
3-iodo-2-propynyl butylcarbamate 55406-53-6	slightly irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	corrosive	1 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
pyrithione zinc 13463-41-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Chromium (III) oxide 1308-38-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Triiron tetraoxide 1317-61-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
trizinc bis(orthophosphate) 7779-90-0	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
3-iodo-2-propynyl butylcarbamate 55406-53-6	Category 1 (irreversible effects on the eye)		rabbit	EPA OPP 81-4 (Acute Eye Irritation)
pyrithione zinc 13463-41-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Chromium (III) oxide 1308-38-9	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Triiron tetraoxide 1317-61-9	not sensitising		guinea pig	Maurer Optimisation Test
trizinc bis(orthophosphate) 7779-90-0	not sensitising			not specified
3-iodo-2-propynyl butylcarbamate 55406-53-6	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
pyrithione zinc 13463-41-7	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Chromium (III) oxide 1308-38-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Triiron tetraoxide 1317-61-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
Triiron tetraoxide 1317-61-9	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Triiron tetraoxide 1317-61-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EPA OPP 84-2 (Mutagenicity Testing)
3-iodo-2-propynyl butylcarbamate 55406-53-6	negative		with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
pyrithione zinc 13463-41-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
pyrithione zinc 13463-41-7	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
pyrithione zinc 13463-41-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Titanium dioxide 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Chromium (III) oxide 1308-38-9	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	negative	oral: gavage		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
pyrithione zinc 13463-41-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture	negative	oral: gavage		mouse	OECD Guideline 475

3:1 (CIT/MIT) 55965-84-9					(Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
3-iodo-2-propynyl butylcarbamate 55406-53-6	not carcinogenic	oral: unspecified	104 w daily	rat	male/female	not specified
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	NOAEL P 300 ppm NOAEL F1 > 750 ppm NOAEL F2 > 750 ppm	two-generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Chromium (III) oxide 1308-38-9	NOAEL > 2.000 mg/kg	oral: feed	90 d 5 d/w	rat	not specified
Triiron tetraoxide 1317-61-9		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Bismuth vanadium tetraoxide 14059-33-7	NOAEL 0,0001 mg/l	inhalation: dust	90 d 6 h/working day	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
3-iodo-2-propynyl butylcarbamate 55406-53-6	NOAEL 0,00116 mg/l	inhalation	90 d	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
pyrithione zinc 13463-41-7	NOAEL 0,5 mg/kg	oral: gavage	104 w daily	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 0.34 mg/m ³	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	5,25 mm ² /s	40 °C		

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	LC50	> 1.000 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Chromium (III) oxide 1308-38-9	LC50	Toxicity > Water solubility	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)])
Chromium (III) oxide 1308-38-9	NOEC	Toxicity > Water solubility	30 d	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 210 (fish early lite stage toxicity test)
Chrome antimony titanium buff rutile 68186-90-3	LC50	> 10.000 mg/l	96 h	Leuciscus idus	DIN 38412-15
Triiron tetraoxide 1317-61-9	LL50	Toxicity > Water solubility	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bismuth vanadium tetraoxide 14059-33-7	LC50	Toxicity > Water solubility	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
trizinc bis(orthophosphate) 7779-90-0	LC50	0,333 mg/l	96 h	Oncorhynchus mykiss	other guideline:
3-iodo-2-propynyl butylcarbamate 55406-53-6	LC50	0,067 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	NOEC	0,0084 mg/l	35 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	LC50	0,06 mg/l	96 h	Pimephales promelas	EPA OPPTS 850.1085 (Fish Acute Toxicity Test mitigated by humic acid)
pyrithione zinc 13463-41-7	LC50	0,0026 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
pyrithione zinc 13463-41-7	NOEC	0,00112 mg/l	32 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Chromium (III) oxide 1308-38-9	LC50	Toxicity > Water solubility	48 h	Ceriodaphnia dubia	other guideline:
Chrome antimony titanium buff rutile 68186-90-3	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triiron tetraoxide	EL50	Toxicity > Water	48 h	Daphnia magna	EU Method C.2 (Acute

1317-61-9		solubility			Toxicity for Daphnia
Bismuth vanadium tetraoxide 14059-33-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
trizinc bis(orthophosphate) 7779-90-0	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	EC50	0,65 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	EC50	0,98 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
pyrithione zinc 13463-41-7	EC50	0,0063 mg/l	96 h	Americamysis bahia	EPA OPP 72-3 (Estuarine/Marine Fish, Mollusk, or Shrimp Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Chromium (III) oxide 1308-38-9	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	other guideline:
3-iodo-2-propynyl butylcarbamate 55406-53-6	NOEC	0,05 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	NOEC	0,013 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
pyrithione zinc 13463-41-7	NOEC	0,0022 mg/l	21 d	Daphnia magna	EPA OPP 72-4 (Fish Early Life-Stage/Aquatic Invert.Life-Cycle Studies)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1.000 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chromium (III) oxide 1308-38-9	EC50	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chromium (III) oxide 1308-38-9	EC10	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chrome antimony titanium buff rutile 68186-90-3	EC50	> 100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chrome antimony titanium buff rutile 68186-90-3	NOEC	> 100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bismuth vanadium tetraoxide 14059-33-7	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bismuth vanadium tetraoxide 14059-33-7	NOEC	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
trizinc bis(orthophosphate) 7779-90-0	NOEC	0,047 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
trizinc bis(orthophosphate) 7779-90-0	IC50	0,268 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	EC50	0,053 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	NOEC	0,0046 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	EC50	0,46 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	NOEC	0,15 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
pyrithione zinc 13463-41-7	EC50	0,0006 mg/l	48 h	Skeletonema costatum	EPA OPP 123-3 (Algal Toxicity, Tiers I and II)
pyrithione zinc 13463-41-7	NOEC	0,00004 mg/l	48 h	Skeletonema costatum	EPA OPP 123-3 (Algal Toxicity, Tiers I and II)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC0	> 1.000 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Chrome antimony titanium buff rutile 68186-90-3	EC10	> 10.000 mg/l	30 min		not specified
Triiron tetraoxide 1317-61-9	EC50	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Bismuth vanadium tetraoxide 14059-33-7	EC10	Toxicity > Water solubility	16 h	Pseudomonas putida	ISO 10712: Determination of the inhibitory effect of water constituents on bacteria (Pseudomonas cell inhibition test)
trizinc bis(orthophosphate)	EC0	0,69 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27

7779-90-0					(Bacterial oxygen consumption test)
pyrithione zinc 13463-41-7	NOEC	0,1 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
3-iodo-2-propynyl butylcarbamate 55406-53-6	not readily biodegradable.	aerobic	25 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	readily biodegradable	aerobic	66 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
pyrithione zinc 13463-41-7	not readily biodegradable.	aerobic	39 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Bismuth vanadium tetraoxide 14059-33-7	< 1,2	42 d		Oryzias latipes	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
3-iodo-2-propynyl butylcarbamate 55406-53-6	3,3 - 4,5			Carassius sp.	not specified
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	173			calculation	not specified
pyrithione zinc 13463-41-7	8,28	30 d		Crassostrea virginica	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Chromium (III) oxide 1308-38-9	2,97		not specified
3-iodo-2-propynyl butylcarbamate 55406-53-6	2,81		not specified
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	8,35	20 °C	EU Method A.8 (Partition Coefficient)
pyrithione zinc 13463-41-7	0,9	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Quartz (SiO ₂) respirable particulates (RCS) >=10% 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Quartz (SiO ₂), <1% respirable 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Chromium (III) oxide 1308-38-9	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Chrome antimony titanium buff rutile 68186-90-3	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Triiron tetraoxide 1317-61-9	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Bismuth vanadium tetraoxide 14059-33-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
trizinc bis(orthophosphate) 7779-90-0	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
3-iodo-2-propynyl butylcarbamate 55406-53-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
pyrithione zinc 13463-41-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080119

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	A(c) Exterior walls of mineral substrate
Phase I (from 1.1.2007):	75 g/l
Phase II (from 1.1.2010):	40 g/l
max. VOC content:	17 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Product is intended for professional use.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.