



# Declaration of Performance

Kingspan Kooltherm® K5 External Wall Board

1002.CPR.2013.K5.007

Unique identification code of the product-type:

Intended use/es:

Manufacturer:

System/s of AVCP:

Designated technical specification

Notified body(ies)

**Kingspan Kooltherm® K5 External Wall Board**

**Thermal insulation for buildings**

**Kingspan Insulation Ltd, Bree Industrial Estate, Castleblayney,  
Co Monaghan, Ireland A75 X966**

**System 1 (Reaction to Fire), System 3 (Other Properties)**

**EN 13166:2012+A2:2016**

**Efectis (NB 1812), AFITI (NB 1168), KIWA BDA (NB 1640)**

Essential characteristics		Performance																		
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	<table border="0"> <tr><td>d<sub>N</sub> 25mm</td><td>1.10</td></tr> <tr><td>d<sub>N</sub> 30mm</td><td>1.35</td></tr> <tr><td>d<sub>N</sub> 40mm</td><td>1.80</td></tr> <tr><td>d<sub>N</sub> 50mm</td><td>2.35</td></tr> <tr><td>d<sub>N</sub> 60mm</td><td>2.85</td></tr> <tr><td>d<sub>N</sub> 70mm</td><td>3.30</td></tr> <tr><td>d<sub>N</sub> 80mm</td><td>3.80</td></tr> <tr><td>d<sub>N</sub> 90mm</td><td>4.25</td></tr> <tr><td>d<sub>N</sub> 100mm</td><td>4.75</td></tr> </table>	d <sub>N</sub> 25mm	1.10	d <sub>N</sub> 30mm	1.35	d <sub>N</sub> 40mm	1.80	d <sub>N</sub> 50mm	2.35	d <sub>N</sub> 60mm	2.85	d <sub>N</sub> 70mm	3.30	d <sub>N</sub> 80mm	3.80	d <sub>N</sub> 90mm	4.25	d <sub>N</sub> 100mm	4.75
	d <sub>N</sub> 25mm	1.10																		
	d <sub>N</sub> 30mm	1.35																		
d <sub>N</sub> 40mm	1.80																			
d <sub>N</sub> 50mm	2.35																			
d <sub>N</sub> 60mm	2.85																			
d <sub>N</sub> 70mm	3.30																			
d <sub>N</sub> 80mm	3.80																			
d <sub>N</sub> 90mm	4.25																			
d <sub>N</sub> 100mm	4.75																			
Thermal conductivity $\lambda_D$ (W/(m.K))	<table border="0"> <tr><td>d<sub>N</sub> 25-44mm</td><td>0.022</td></tr> <tr><td>d<sub>N</sub> 45-100mm</td><td>0.021</td></tr> </table>	d <sub>N</sub> 25-44mm	0.022	d <sub>N</sub> 45-100mm	0.021															
d <sub>N</sub> 25-44mm	0.022																			
d <sub>N</sub> 45-100mm	0.021																			
Thickness tolerance	T1																			
Reaction to fire	Reaction to fire	C-s2,d0																		
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD																		
Durability of thermal resistance against heat, weathering, ageing/ degradation	Durability Characteristics	NPD																		
	Dimensional stability under specified temperature and humidity condition	DS(70,90)																		
		DS(-20,-)																		



# Declaration of Performance

	Thermal conductivity $\lambda_D$ (W/(m.K))	d <sub>N</sub> 25-44mm 0.022 d <sub>N</sub> 45-100mm 0.021
	Determination of the aged values of thermal resistance and thermal conductivity	RD and $\lambda_D$
Compressive strength	Compressive stress or compressive strength	CS(Y)100
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Closed cell content	CV
Water vapour permeability	Water vapour transmission	NPD
	Closed cell content	NPD
Continuous Glowing Combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....  
**Aiveen Kearney**  
 Managing Director, Ireland  
 Date signed: 9<sup>th</sup> February 2024  
 Issue Number: 007



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.ie](mailto:literature@kingspaninsulation.ie).